

BOTTLE STICKERS

RFID Bottle Sticker is designed for high level security applications to achieve anti-counterfeiting purpose. Once the stickers stick to the material, it will be unable to remove well until it is broken. It is made of environment-friendly material, can be printed with ribbons directly.



酒类防转移标签

RFID酒类标签是一款易碎防转移标签，采用特殊工艺制作，支持打印、写码加密等工艺。采用RFID酒类标签进行酒类的防伪和溯源，通过RFID标签记录每瓶酒的生产、仓储、销售出厂的全过程，可以有效的实现防伪、防窜货。

NTAG213 TT

NTAG414 DNA TT



SKU 型号	DIMENSION 尺寸	Antenna Size 天线尺寸	MATERIAL 面料选择	PACKAGE 包装方式	LF 低频	NFC 高频	UHF 超高频	CHIP 芯片
LAP-BT	25x L50mm	D21, tie 23mm	Fraigle Paper	on Roll	✗	✓	✗	NTAG213 TT / NTAG424 DNA
LAP-BT	D25x L60mm	D21, tie 35mm	Fraigle Paper	on Roll	✗	✓	✗	NTAG213 TT / NTAG424 DNA
LAP-BT	D25x L125mm	D21, tie 100mm	Fraigle Paper	In Roll	✗	✓	✗	NTAG213 TT / NTAG424 DNA

Mark: Stickers Size will be more than 2mm from the edge of antenna!
注: 只要比天线尺寸两边各大2mm, 均可做成不干胶标签等成品!

Personalizations:

- Printing Logo
- Printing QR,Barcode
- Chip Encoding

支持定制工艺:

- 印刷Logo
- 印刷号码、二维码
- 写码加密

13.56Mhz HF RFID 高频RFID	IC Type 芯片名称	Read/Write 读写	Read/Write Memory 容量	UID byte 内码	Protocol 协议	Brand 品牌	Comments 备注
	NTAG213	R/W	144byte	7	ISO14443A / NFC Type2	NXP	★
	NTAG215	R/W	504byte	7	ISO14443A / NFC Type2	NXP	
	NTAG216	R/W	888byte	7	ISO14443A / NFC Type2	NXP	
	MIFARE CLASSIC EV1 1K	R/W	1024bit	4/7	ISO14443A	NXP	★
	FM11RF08	R/W	1K byte	4	ISO14443A	Fudan	
	MIFARE CLASSIC EV1 4K	R/W	4K byte	4/7	ISO14443A	NXP	
	MIFARE Ultralight EV1	R/W	384bit	7	ISO14443A	NXP	
	MIFARE Ultralight EV1	R/W	1024bit	7	ISO14443A	NXP	
	MIFARE Ultralight C	R/W	1536 bit	7	ISO14443A	NXP	
	MIFARE DESFire 2K <i>(ev1/ev2/ev3)</i>	R/W	2K byte	7	ISO14443A	NXP	
	MIFARE DESFire 4K <i>(ev1/ev2/ev3)</i>	R/W	4K byte	7	ISO14443A	NXP	
	MIFARE DESFire 8K <i>(ev1/ev2/ev3)</i>	R/W	8K	7	ISO14443A	NXP	
	MIFARE DESFIRE LIGHT	R/W	1K byte	7	ISO14443A / NFC Type 4	NXP	
	MIFARE Plus SE 1K	R/W	1K byte	4/7	ISO14443A	NXP	
	MIFARE Plus EV2 2K	R/W	2K byte	7	ISO14443A	NXP	
	MIFARE Plus EV2 4K	R/W	4K byte	7	ISO14443A	NXP	
	I CODE SLIX	R/W	1024bit	7	ISO15693/18000-3	NXP	
	I CODE SLIX-L	R/W	512bit	7	ISO15693/18000-3	NXP	
	I CODE SLIX-S	R/W	2048bit	7	ISO15693/18000-3	NXP	
ST25TN01K	R/W	1664bit	7	ISO14443A / NFC Type 2	ST	★	
FELICA LITE S	R/W	224byte	7	NFC Type 3	SONY		
ST25TV02K	R/W	2048bit	7	ISO15693 / NFC Type 5	ST		
TAG-IT 256	R/W	256bit	7	ISO15693 /18000-3	TI		
TAG-IT 2048	R/W	2048bit	7	ISO15693 /18000-3	TI		

1byte = 8bit

ULTR HIGH Frequency 840-960Mhz	IC Type 芯片名称	EPC EPC容量	USER 用户区	TID TID容量	Brand 品牌	TID Code 编码	Comments 备注
	Higgs 3	96	512	32	Alien	E2003412	
	Higgs-EC	128	128	32	Alien	E2003811	★
	Higgs 9	96-496	688	32	Alien	E2003821	
	Ucode 8	128	0	32	NXP	E2806894	
	Ucode 9	96	0	0	NXP	E2806995	★
	Ucode DNA	224	3072	32	NXP	E2C06892	
	Monza 4i	256	480	32	IMPINJ	E2801114	
	Monza 4D	128	32	32	IMPINJ	E2801100	
	Monza 4E	496	128	32	IMPINJ	E280110C	
	Monza 4QT	128	512	32	IMPINJ	E2801105	
	Monza R6	96	0	0	IMPINJ	E2801160	
	Monza R6-P	128	32	32	IMPINJ	E2801170	
	M730	128	0	32	IMPINJ	E2801191	
	M750	96	32	32	IMPINJ	E2801190	
	EM4425	480	1056	32	EM	E200B112	
	Qstar-71GB-O	496	128	32	Quanray坤锐	E280F337	
Qstar-73GB-O	128	512	32	Quanray坤锐	E280F336		
Qstar-73GB-O-V	64-512	128-528	32	Quanray坤锐	E280F338		

100-150Khz Low Frequency	IC Type 芯片名称	Read/Write 读写	Memory 容量	Protocol 协议	Brand 品牌	Comments 备注
	TK4100	R/O	64bit	——		★
	EM4200	R/O	64bit	——	EM	
	EM4550	R/W	1K bit	——	EM	
	EM4069	R/W	128bit	——	EM	
	T5577	R/W	363bit	ISO11784/785	ATMEL	★
	EM4305	R/W	512bit	ISO11784/785	EM	
	HITAG 1	R/W	2K bit	——	NXP	
	HITAG 2	R/W	256bit	——	NXP	
	HITAG S256	R/W	256bit	ISO11784/785	NXP	